

Cargo Equipment Solutions, Inc.

12301 SW 128 Court, Unit 104, Miami, Florida 33186

Phone: 305-259.4537 / 305-259.4538 / Fax: 305-259.4539 / U.S. Toll Free: 877-813.0251

Email: sales@cargo equipmentsolutions.com

POWER PACK FOR REEFERS - 40 PLUGS



PHOTOS FOR REFERENCE ONLY, FINAL PRODUCT MAY CHANGE DEPENDING ON THE QUANTITY OF PLUGS REQUIRED.

POWER PACK:	Model:	CES-PP5/400-60HZ
GENERATOR:	Brand:	STAMFORD
	Model:	HCI-544C1
	STAND BY (KVA/KW):	562/450
	PRIME POWER (KVA/KW):	512/410
	HERTZ:	60
	AC VOLTS:	460
	PHASE:	3
ENGINE:	Brand:	CUMMINS
	Model:	KTA19-G3
	Emmissions (EPA Regulations)	N/A
	Type:	4 Cycle water cooled diesel engine
	Number of Cylinders:	6
	Operation Temperature Range:	26C - 55C
	Oil Tank Capacity (Lts):	50
	Fuel Tank:	2,500 Lts with manual fuel pump
Fuel Consumption at 75% (11.25 kw):	86 Lts/Hr.	
	Starting System:	24 Volts
SYSTEM:	Control Panel:	ComAp MRS-16 auto/manual model
	Instruments:	On/Off Switch
		Voltimeter
		Amperimeter
		Frequence reader
		2 emergency stop buttons (one inside / one outside)
		Failure Sound Alarm
		Hourmeter
		Tachometer (RPM)
		Water Temperature Indicator Display with emergency shut off sensor
	Oil Pressure Indicator Display with emergency shut off sensor	
	Over Drive emergency shut off switch	
MCCB:	Inside:	2 units 400A MCCB for sockets, 2 units 400A MCCB for stand by use.
	Outside:	40 sockets 32A 4P in two sides of container, each with separate 32A breaker
CANOPY:	Size:	20 FT Container with CSC/CCS certificate.
	External Dimmensions (mm):	6096 L x 2438 W x 2591 H
	Weight (Kg):	9,000 oil and coolant included. / Fuel not included.
OTHERS:		2 flameproof lights inside container
		Starting Batteries with Master Switch
		Customer Logo
		Container Number & Shipping Mark
		Removable Roof for easy mantaincement Lateral ladder
FACTORY STANDARDS:	ISO	9001:2000
		14001:2004

MCCB = MASTER CIRCUIT CONTROL BREAKER

Specifications may change without notice.