

Cargo Equipment Solutions, Inc.

12301 SW 128 Court, Unit 104, Miami, Florida 33186
 Phone: 305-259.4537 / 305-259.4538 / Fax: 305-259.4539 / U.S. Toll Free: 877-813.0251
 Email: sales@cargo equipmentsolutions.com

POWER PACK FOR REEFERS - 60 PLUGS



PHOTOS FOR REFERENCE ONLY, FINAL PRODUCT MAY CHANGE DEPENDING ON THE QUANTITY OF PLUGS REQUIRED.

POWER PACK:	Model:	CES-PP5/600-60HZ	
GENERATOR:	Brand:	STAMFORD	
	Model:	HCI-544F1	
	STAND BY (KVA/KW):	850/680	
	PRIME POWER (KVA/KW):	775/620	
	HERTZ:	60	
	AC VOLTS:	460	
	PHASE:	3	
ENGINE:	Brand:	CUMMINS	
	Model:	KT38G	
	Emmissions (EPA Regulations)	N/A	
	Type:	4 Cycle water cooled diesel engine	
	Number of Cylinders:	12	
	Operation Temperature Range:	26C - 55C	
	Oil Tank Capacity (Lts):	135	
	Fuel Tank:	1,000 Lts with manual fuel pump	
Fuel Consumption at 75% (11.25 kw):	118 Lts/Hr.		
	Starting System:	24 Volts	
SYSTEM:	Control Panel:	ComAp MRS-16 auto/manual model	
	Instruments:	On/Off Switch Voltmeter Amperimeter Frequence reader 2 emergency stop buttons (one inside / one outside) Failure Sound Alarm Hourmeter Tachometer (RPM) Water Temperature Indicator Display with emergency shut off sensor Oil Pressure Indicator Display with emergency shut off sensor Over Drive emergency shut off switch	
	MCCB:	Inside: Outside:	
		2 units 400A MCCB for sockets, 2 units 400A MCCB for stand by use. 60 sockets 32A 4P in two sides of container, each with separate 32A breaker	
	CANOPY:	Size:	20 FT Container with CSC/CCS certificate.
		External Dimmensions (mm):	6096 L x 2438 W x 2591 H
		Weight (Kg):	13,000 oil and coolant included. / Fuel not included.
	OTHERS:		2 flameproof lights inside container Starting Batteries with Master Switch Customer Logo Container Number & Shipping Mark Removable Roof for easy mantaincement Lateral ladder
		FACTORY STANDARDS:	ISO

MCCB = MASTER CIRCUIT CONTROL BREAKER

Specifications may change without notice.